

Claims:

1. Bicycle trailer with a chassis formed of at least one frame part, the bicycle trailer comprising: at least one bumper which is positioned on the outside of a frame part of the chassis and projects past the outside of the frame part in at least one direction.
2. Bicycle trailer according to claim 1, wherein the bumper has a greater overall height than the frame part.
3. Bicycle trailer according to claim 1, wherein the bumper projects past at least one edge or one end of the frame part.
4. Bicycle trailer according to claim 1, wherein the bumper extends sideways past the chassis far enough to at least partially cover the front or rear space between the wheel and the chassis.
5. Bicycle trailer according to claim 2, wherein the bumper extends sideways past the chassis far enough to at least partially cover the front or rear space between the wheel and the chassis.
6. Bicycle trailer according to claim 3, wherein the bumper extends sideways past the chassis far enough to at least partially cover the front or rear space between the wheel and the chassis.

7. Bicycle trailer according claim 1, wherein the bumper is hollow.
8. Bicycle trailer according claim 7, wherein the bumper is formed as a tube.
9. Bicycle trailer according to claim 8, wherein at least one of the ends of the bumper is capped with a plug.
10. Bicycle trailer according to claim 1, wherein the bumper takes on a weight-bearing function of the chassis.
11. Bicycle trailer according to claims 1, wherein the bumper is positioned in a front area of the chassis and the bumper is formed to hold a drawbar for the bicycle trailer.
12. Bicycle trailer according to claim 11, wherein the drawbar is detachably connected to the bumper.
13. Bicycle trailer according to claim 1, further comprising at least one storage area in the bumper.
14. Bicycle trailer according to claim 7, further comprising at least one storage area in the bumper.
15. Bicycle trailer according to claim 1, further comprising add-on parts located on the bumper.

16. Bicycle trailer according to claim 1, wherein bumpers are positioned for protection of the front and/or rear corners.
17. Bicycle trailer according to claim 1, wherein the bumper is connected to the frame part by a detachable connection.
18. Bicycle trailer according to one of the claim 1, wherein the bumper is positioned at about the height of a wheel hub of the bicycle trailer.